

Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata 	Dimenzije a x b x c	Težina	MOTORNİ KONTAKTORI CNN, naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
20	3.0	1 0	45x48x57	0.17	CM1 10	1547
		0 1				
25	4.5	0 0	45x71x72,2	0.25	CNN 9 00	1614
		1 0			CNN 9 10	1654
25	4.5	0 0	45x71x72,2	0.25	CNN 9 004 ; CNN 9 00 22	1756
25	5.7	0 0	45x71x72,2	0.25	CNN 12 00	1769
		1 0			CNN 12 10	1841
25	5.7	0 0	45x71x72,2	0.25	CNN 12 004 ; CNN 12 00 22	1966
30	7.5	1 0	45x71x72,2	0.26	CNN 18 10	2188
		0 1				
40	11	0 0	45x71x72,2	0.275	CNN 25 00	2841
40	15	0 0	45x71x72,2	0.290	CNN 30 00	3362
50	15	0 0	45x80x84,6	0.355	CNN 32 00	4046
50	18.5	0 0	45x80x84,6	0.355	CNN 40 00	4952
80	22	0 0	55x120x109	0.845	CNN 50 00	7030
85	30	0 0	55x120x109	0.850	CNN 60 00	8894
85	33	0 0	70x142x123	0.900	CNN 70 00	10444
90	37	0 0	70x142x123	1.280	CNN 80 00	13056
95	45	0 0	70x142x123	1.300	CNN 90 00	14760
100	55	0 0	70x142x123	1.350	CNN 100 00	15800
					Dodaci (blokovi pomoćnih kontakata)	RSD
		0 1	45x48x38	0.04	BPO (40, 31, 22, 13, 04), prednji	853
		3 1				
		2 2				
		1 3				
		0 4				
		1 0		0.013	BP1 (1NO ili 1NC), stranični	364
		0 1				
		1 1	40x35x38	0.03	BP2 11 (1NO+1NC), prednji	437
		1 1	55x10x46	0.05	BP5 11 (1NO+1NC), stranični	739
		1 1	55x10x46	0.03	BP3 11 (1NO+1NC), stranični	401
		2 2	40x35x38	0.04	BP4 22 (2NO+2NC), prednji	524
		4 0	40x35x38	0.04	* BP4 40 (4NO+0NC), prednji	524
		2 2	40x35x38	0.04	BP2 N 11 (1NO+1NC), prednji	739
		2 2	40x35x38	0.04	BP4 N 22 (2NO+2NC), prednji	918



Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	MOTORNI KONTAKTORI CNM, naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
63	22	2 2	87x114x111	1.30	CNM 45 22	8418
		4 4	112x114x111	1.40	CNM 45 44	10009
72	30	2 2	87x114x111	1.30	CNM 60 22	10137
		4 4	112x114x111	1.40	CNM 60 44	11723
100	37	2 2	100x132x142	2.27	CNM 75 22	15349
		4 4	125x132x142	2.37	CNM 75 44	16843
110	45	2 2	100x132x142	2.28	CNM 90 22	18977
		4 4	125x132x142	2.38	CNM 90 44	20640
115	55	2 2	100x132x142	2.29	CNM 110 22	20371
		4 4	125x132x142	2.39	CNM 110 44	21995
160	75	2 2	135x180x189	5.10	CNM 140 22	30893
		4 4	135x180x189	5.60	CNM 140 44	33138
200	90	2 2	135x180x189	5.20	CNM 170 22	34762
		4 4	162x180x189	5.70	CNM 170 44	37385
250	110	2 2	135x180x189	5.30	CNM 200 22	42295
		4 4	162x180x189	5.80	CNM 200 44	44973
300	132	2 2	160x200x226	8.40	CNM 250 22	57302
		4 4	187x200x226	8.90	CNM 250 44	60138
390	160	2 2	160x200x226	8.50	CNM 315 22	71395
		4 4	187x200x226	8.90	CNM 315 44	73617
400	200	2 2	160x200x226	8.50	CNM 400 22	86325
		4 4	187x200x226	8.90	CNM 400 44	88570
700	250	2 2	220x250x225	13.50	CNM 450 22	141258
800	315	2 2	220x250x225	14.00	CNM 550 22	181799
1000	400	2 2	280x307x291	26.40	CNM 700 22	200818
1100	500	2 2	280x307x291	27.80	CNM 860 22	281103
1200	580	2 2	334x490x345	51.00	CNM 1000 22	778110
		Težina(kg)	Dodatci			
			RC elementi za CNNP ; CNN9 - CNN 40			408
		0.021	dodatci za priključke za (CNN 32 - CNN 40) za priključenje vodiča do 25mm ² , (2 komada),br.dela:601478			874
		0.14	Set od 6 štيتnika (poklopca) za terminale kontaktora (CNM 75-CN110),br.dela:603311			2913
		0.15	Set od 6 štيتnika (poklopca) za terminale kontaktora (CNM 140-CN200),br.dela:604128			3495
Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	MOTORNI KONTAKTORI CN, naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
23	4.7	1 1	68x68x78,5	0.425	CN 10	3492
		2 0				
		0 2				
30	7.5	1 1	68x68x78,5	0.425	CN 16	3706
		2 0				
		0 2				
35	12	2 2	85x100x103	0.930	CN 25	8143
45	15	2 2	85x100x103	0.935	CN 40	10201
130	40	2 2	192x190x130	5.50	CN 80	29712
160	55	2 2	192x190x130	5.60	CN 110	35539
220	90	2 2	212x234x180	9.50	CN 170	64066
300	132	2 2	212x234x180	9.70	CN 250	90405



Nazivna nominalna struja le kod Un=400 V, AC 6b	Snaga konden. kod Un=400V, AC 6b	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	Kondenzatorski kontaktori CNNK, naizmenični napon upravljanja	Cena
(A)	(kVar)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
18	2.5	1 0	45x71x72,2	0.25	CNNK 2,5	2046
18	5	1 0	45x71x72,2	0.25	CNNK 5	2285
29	7.5	0 0	45x71x72,2	0.275	CNNK 7,5	2492
14	10	2 0	45x72,2x108	0.314	CNNK 10 20	3161
14	10	1 1	45x72,2x108	0.314	CNNK 10 11	3161
18	12.5	2 0	45x72,2x108	0.316	CNNK 12 20	3353
18	12.5	1 1	45x72,2x108	0.316	CNNK 12 11	3353
22	15	2 0	45x72,2x108	0.318	CNNK 15 20	3800
22	15	1 1	45x72,2x108	0.318	CNNK 15 11	3800
29	20	1 0	45x80x121,3	0.333	CNNK 20 10	3991
36	25	1 0	45x80x121,3	0.404	CNNK 25 E 10	4950
36	25	1 0	45x80x121,4	0.404	CNNK 25 10	5271
44	30	1 0	45x80x121,3	0.414	CNNK 30 10	5718
50	40	1 0	55x120x109	0.875	CNNK 40 10	8145
72	50	1 0	55x120x109	0.880	CNNK 50 10	8783
87	60	1 0	55x120x109	0.920	CNNK 60 10	10060
101	70	1 0	70x142x123	1.320	CNNK 70 10	14890
108	75	2 2	130x158x145	2	CNKM 75 22	22326
108	75	2 2	130x158x145	2.47	CNKM 80 22	23155
Nazivna nominalna struja le kod Un=230 V, AC 15/AC 14		Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	POMOĆNI KONTAKTORI, naizmenični napon upravljanja	Cena
(A)		ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
6		4 0	45x48x56	0.17	CP0	1544
		3 1				
		2 2				
10		4 0	45x71x72,2	0.25	CNNP	1667
		3 1				
		2 2				
		1 3				
		sve izvedbe kao CNNP	45x71x72,2	0.27	CNNP F	2244
Nazivna nominalna struja le kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 1	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	TERMIČKI KONTAKTORI, naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
65	43	2 2	45x129x113	0.59	TKN 65 00	6483
115	76	2 2	87x172x111	1.50	TKN 115 22	11400
130	85	2 2	100x158x140	2.42	TK 130 22	19835
175	115	2 2	100x158x140	2.42	TK 175 22	21895



Nazivna nominalna struja Ie kod Un=400 V, AC 2/AC3	Nazivna nominalna snaga Pn, Un=400 V, AC 2/AC3	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	Kontaktori MBCNN i MBCNM (mehanička i električna blokada)	Cena
(A)	(kW)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
6.5	2.2	0 0	83x110x56	0.41	MBCM1 00	4356
6.5	2.2	1 0	83x110x56	0.41	MBCM1 10	4711
9	4.5	0 0	100x72,2x71	0.503	MBCNN 9 00	4889
9	4.5	1 1	120x72,2x71	0.505	MBCNN 9 11	5630
12	5.7	0 0	100x72,2x71	0.503	MBCNN 12 00	5422
12	5.7	1 1	120x72,2x71	0.505	MBCNN 12 11	6163
18	7.5	0 0	100x72,2x71	0.523	MBCNN 18 00	6133
18	7.5	1 1	120x72,2x71	0.525	MBCNN 18 11	6874
25	11	1 0	100x72,2x71	0.553	MBCNN 25 10	8311
30	11	1 0	100x72,2x71	0.553	MBCNN 30 10	9289
32	15	1 0	120x80x84,6	0.713	MBCNN 32 10	11111
40	18.5	1 0	120x80x84,6	0.713	MBCNN 40 10	13156
45	22	1 0	160x140x111	2.80	MBCNN 50 10	19911
45	22	2 1	160x140x111	2.80	MBCNN 50 21	21393
60	30	1 0	160x140x111	2.82	MBCNN 60 10	24889
60	30	2 1	160x140x111	2.82	MBCNN 60 21	26370
65	33	1 0	160x140x111	2.88	MBCNN 70 10	31111
65	33	2 1	160x140x111	2.88	MBCNN 70 21	32593
75	37	1 0	200x150x102	3.78	MBCNN 80 10	37778
75	37	2 1	200x150x102	3.78	MBCNN 80 21	39259
90	45	1 0	200x150x102	3.81	MBCNN 90 10	40445
90	45	2 1	200x150x102	3.81	MBCNN 90 21	41926
110	55	2 1	200x150x102	5.78	MBCNM 110 21	57333
140	75	2 1	270x210x189	14.20	MBCNM 140 21	88445
170	90	2 1	270x210x189	14.40	MBCNM 170 21	102222
200	105	2 1	270x210x189	14.60	MBCNM 200 21	120000
250	132	2 1	310x235x226	23.00	MBCNM 250 21	164445
315	160	2 1	310x235x226	23.20	MBCNM 315 21	200000
400	200	2 1	310x235x226	23.40	MBCNM 400 21	248889
Dodatci						
				0.003	MB2, mehanička blokada za CNN9-CNN40	1052
					MB3, mehanička blokada za CNN50-CNN90	4593
Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	Bežumni kontaktori CNB jednosmerni napon upravljanja	Cena
(A)	(kW)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 24, 110, 220 DC	RSD
10	4.5	4 0	45x90x129	0.60	CNNPB	3024
		3 1				
		2 2				
		1 3				
		0 4				
25	4.5	1 0			CNNB 9 10	3024
25	5.7	1 0			CNNB 12 10	3312
30	7.5	3 2			CNNB 18 10	3755
40	11	0 0			CNNB 25 00	3996
		2 2			CNNB 30 00	4668



Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata y t	Dimenzije a x b x c	Težina	MOTORNI KONTAKTORI jednosmerni napon upravljanja	Cena
(A)	(kW)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 24, 110, 220 DC	RSD
16		4 0	45x75x85	0.37	CNNP 40 EG	3208
25	4.5	1 0	50x71x72,2	0.25	CNN 9 10	2291
25	5.7	1 0	50x71x72,2	0.25	CNN 12 10	2474
30	7.5	1 0	50x71x72,2	0.26	CNN 18 10	2719
40	11	1 0	50x71x72,2	0.275	CNN 25 10	3544
40	15	1 0	50x71x72,2	0.290	CNN 30 10	3880
50	15	1 0	50x80x84,6	0.36	CNN 32 10	4506
50	18.5	1 0	50x80x84,6	0.36	CNN 40 10	5480
85	22	1 0	60x120x109	0.85	CNN 50 10	7607
85	30	1 0	60x120x109	0.85	CNN 60 10	9317
90	33	1 0	75x142x123	0.90	CNN 70 10	11456
95	37	1 0	75x142x123	1.28	CNN 80 10	14865
105	45	1 0	75x142x123	1.30	CNN 90 10	16918
105	50	1 0	75x142x123	1.350	CNN 100 10	18023
115	55	2 1	100x132x142	2.29	CNM 110 21 (11)	21995
		4 3	125x132x142	2.39	CNM 110 43 (33)	23828
250	75	2 1	135x180x189	5.10	CNM 140 21 (12)	31923
		4 3	162x180x189	5.60	CNM 140 43 (34)	34336
250	90	2 1	135x180x189	5.20	CNM 170 21 (12)	36658
		4 3	162x180x189	5.70	CNM 170 43 (34)	39713
250	105	2 1	135x180x189	5.30	CNM 200 21 (12)	42767
		4 3	162x180x189	5.80	CNM 200 43 (34)	45822
350	132	2 1	160x200x226	8.40	CNM 250 21 (12)	59569
		4 3	187x200x226	8.90	CNM 250 43 (34)	62624
390	160	2 1	160x200x226	8.50	CNM 315 21 (12)	71788
		4 3	187x200x226	8.90	CNM 315 43 (34)	74843
450	200	2 1	160x200x226	8.50	CNM 400 21 (12)	88590
		4 3	187x200x226	8.90	CNM 400 43 (34)	91645
23	4.7	11 02 20	68x68x78,5	0.425	CN 10	4674
30	7.5	11 02 20	68x68x78,5	0.425	CN 16	4964
35	12	2 2	85x100x103	0.930	CN 25	10906
45	15	2 2	85x100x103	0.935	CN 40	13655
130	40	2 2	192x190x130	5.50	CN 80	36016
160	55	2 2	192x190x130	5.60	CN 110	43653
220	90	2 2	212x234x180	9.50	CN 170	77898
300	132	2 2	212x234x180	9.70	CN 250	112265
SKLOPNICI U KUĆIŠTU naizmenični napon upravljanja						Cena
25	4	1 0	100x191x123		PN 9	3737
25	5.5	2 2	100x191x123		PN 12	4357
25	7.5	2 2	100x191x123		PN 16	5054
35	11	2 2	100x191x123		PN 22	6038
39	15	2 2	100x191x123		PN 30	7561

Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC2/AC3	Broj pomoćnih kontakata y t	Dimenzije a x b x c	Težina	SKLOPNICI sa BIMETALNIM RELEJEM U KUĆIŠTU naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
25	4		100x191x123		PNRT 9	7687
25	5.5	1 2	100x191x123		PNRT 12	8406
25	7.5	1 2	100x191x123		PNRT 16	9105
35	11	1 2	100x191x123		PNRT 22	10681
39	15	1 2	100x191x123		PNRT 30	12204
25	4	1 0	100x191x123		PNRG 9	7238
25	5.5	2 2	100x191x123		PNRG 12	7958
25	7.5	2 2	100x191x123		PNRG 16	8654
35	11	2 2	100x191x123		PNRG 22	10230
39	15	2 2	100x191x123		PNRG 30	11756

REZERVNI DELOVI ZA KONTAKTORE					
Cena (RSD)					
Tip	Glavni kontakti komplet	Jedan blok pomoćnih kontakata	KALEM naizmenični napon upravljanja	KALEM jednosmerni napon	Lučna komora
CNM 36	2889	730	1149	1264	
CNM 45	3473	730	2505	2755	
CNM 60	5487	730	2505	2755	
CNM 75	7909	730	4420	4862	3255
CNM 90	9601	730	4420	4862	3255
CNM 110	10623	730	4420	4862	3255
CNM 140	13862	1167	7338	8074	8317
CNM 170	15497	1167	7338	8074	8317
CNM 200	21509	1167	7338	8074	8317
CNM 250	28775	1167	14145	15559	16693
CNM 315	40023	1167	14145	15559	16693
CNM 400	47657	1167	14145	15559	16693
CN 10	1448	1138	1444	1588	
CN 16	1535	1138	1444	1588	
CN 25	2597	1839	2888	3177	1550
CN 40	3169	1839	2888	3177	1761
CNO 30	3487	1839	2888	3177	2668
CN 63	6750	2948	5579	6135	2471
CNO 63	7424	2948	5579	6135	2471
CN 80	9981	2948	7935	8729	3880
CN 110	12082	2948	7935	8729	4935
CNO 110	13290	2948	7935	8729	4935
CN 170	21669	2948	15324	16856	11282
CN 250	31081	2948	15324	16856	11282
CNO 250	34189	2948	15324	16856	11282
CNB 50	7267	2948		7845	2471
TK 115	6596	1430	2505		
TK 130	9485	1430	4420		3254
TK 175	12753	1430	4420		3254
CM1			1139		
CNP 21/31			1139		
CNM 9,12,16,22,30,36			1139		
CNN 9,12,18,25			1137		
CNN 32,40,50,60			1197		
CNN 70,80,90			1739		
TK 25, 35, 65			1137		
CNB 9, 21, 31, 12				2112	
CNB 16, 22, 30				2214	
- Kod izvedbi "pojačanih" kompleta glavnih kontakata, gore navedene cene se povećavaju za 30%					
- Cene kalema se odnose samo na standardne napone upravljanja					
- Za nestandardne napone cena je 10% veća					
Pomoćni kontakti za UTKN					RSD
CN 10/16					943
CN 25/40					1017
CNM 36-110					5412
CN 63-250					5567